

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.


**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

con. WO 97/48669
and US 6,348,638

METHOD FOR REMOVING BY-PRODUCTS OBTAINED WHEN PRODUCING ACRYLIC / OR METHACRYLIC ACIDS

Patent number: EP0925272
Publication date: 1999-06-30
Inventor: HAMMON ULRICH (DE); PIES WOLFGANG (DE); RAUH ULRICH (DE);
SCHLIEPHAKE VOLKER (DE)
Applicant: BASF AG (DE)
Classification:
- international: C07C57/04; F23G5/00
- european:
Application number: EP19970928252 19970619
Priority number(s): DE19961024674 19960620; WO1997EP03216 19970619

Also published as:

 WO9748669
US6348638
DE1962467
EP0925272

Abstract not available for EP0925272

Abstract of correspondent: **US6348638**

In a process for the disposal of low, medium, and high-boiling secondary components formed during the preparation of (meth)acrylic acid the gaseous low-boiling secondary components are burned, whilst low-boiling and medium-boiling secondary components that are dissolved in water optionally together with high-boiling secondary components treated with solvent are added

